

Succeed Life Science Pte. Ltd.

61 Tuas View Walk 2, Singapore 637630 Telephone: +65 6898 9909 Fax: +65 6862 3669



PRODUCT DATA SHEET

POWDER NBR NPX-2235

PRODUCT DESCRIPTION:

NPX-2235	is processed through special technics after butadiene and acrylonitrile are copolymerized
	under low temperature.

NPX-2235 is powder form macromolecule rubber.

NPX-2235 is environmental friendly material. It has passed various measures for SGS Test and does not contain 16P.

PRODUCT CHARACTERISTICS:

- A. Controls plasticizer from precipitation can absorb low molecular plasticizers after addition, thereby to reduce or avoid low molecular plasticizers from precipitation
- B. Environmental friendly will not cause environmental pollution
- C. Not harmful to human body NPX-2235 is suitable to use in food and human body contact PVC products industries.

PROPERTIES OF APPLICATIONS:

NPX-2235 can provide the following properties to PVC products:

- Heat and low temperature resistance properties
- Oil resistance property
- Increases elongation at break
- Improves compressive deformation properties
- Improves product's rebound resilience
- Low temperature flexibility

APPLICATIONS:

NPX-2235 can be used in thermoplastic elastomer materials to fully or partially replace of liquid plasticizer.

•	PVC Cables and Wires	•	Friction materials etc.
•	Auto-mobile & construction use sealant,	•	Plumbing pipe gasket seal
	refrigerator sealant		
•	Auto-mobile fuel pipe, hosepipe	•	Auto mobile dust cover, Mine-use protective
			cover
•	Rubber Conveyer belt, V-belt	•	Thin film, leatheroid, banner
•	Shoe products (Galoshes and Safety boots)		

NOTE:



Succeed Life Science Pte. Ltd.

61 Tuas View Walk 2, Singapore 637630 Telephone: +65 6898 9909 Fax: +65 6862 3669

TECHNICAL DATA:

Polymer Name	NPX-2235		
Method of polymerization	Low temperature polymerization		
Acrylonitrile content (%)	27		
Mooney Viscosity ML1+4 @100℃	48		
Parting agent	Chemicals		
Particle size (mesh)	40		
Degree of crosslinking	Linear		
Specific Gravity	0.98		
Stabilizer	Non-pollution		
Emulsifier	Aliphatic acid		
Appearance	Powder form		
Packaging	25KG		
Application and Properties	PVC products		